



RECOMMENDED PANEL CUTOUT

**MATERIALS:**

PLASTIC HOUSING: ENGINEERING THERMOPLASTIC  
FLAMMABILITY RATING UL 94V-0.

CONTACTS: PHOSPHOR BRONZE

PLATING: GOLD PLATING OVER NICKEL IN CONTACT.

TIN PLATING OVER NICKEL IN SOLDER AREA.

SHIELD: BRASS PLATING NICKEL ALLOY.

**ELECTRICAL:**

CURRENT RATING: 1.5 AMPERES MAX. @ 25°C.

VOLTAGE RATING: 150 VAC MAX.

VOLTAGE: 60 VDC.

DIELECTRIC WITHSTANDING VOLTAGE:

1000VAC, RMS, 60Hz, 1MIN.

INSULATION RESISTANCE : 500 MEGOHMS MIN.

OPERATING TEMPERATURE: 0°C TO +70°C.

STORAGE TEMPERATURE: -40°C TO +80°C.

RoHS COMPLIANT

P/N. 6u": 3046105605

15u": 3046105705

30u": 3046105805

50u": 3046105905

※凡標註 △ 記號者為品管管制尺寸。

設計DR. Kathy Chung 2012/06/11	核准APPD. Jerry 2012/06/11	容許公差 .XXX ±0.10 .XX ±0.25 .X ±0.38 X ±0.50 ANG ±3°	TOLERANCE	品名 ARTICLE 3046S 8P8C JACK
版本說明 更正側視圖 STAND OFF 與實品相符, 圖面發D版。		REVISION NOTE		圖號 DWG NO. 3046105605
				單位 UNIT mm
				比例 SCALE 2/1
				張數 SHEET 1/1
				版本 REV. D